



Miner Lamp Bracket Kit

Kit contains:

- Lamp Bracket
- Cord holder tab

To install:

1. Cap shell must be free from dirt, oil, grease or any material that will prevent the bracket adhesive from adhering. Clean the shell with mild soap and warm water. Dry thoroughly.
2. Peel the protective paper off of the back side of the lamp bracket. Do not touch exposed adhesive .
3. With widest part of bracket slot facing up, place the bracket on the cap shell (see Figure 1) and press in place, squeezing out any air bubbles.
4. Repeat the above procedure for the cord holder tab which goes on the back of the cap (see Figure 2).




Figure 1

Front View



Figure 2

Back View



Americas:
E.D. Bullard Company
1898 Safety Way
Cynthiana, KY 41031-9303
Toll free: 877-BULLARD
(285-5273)
Tel: 859-234-6616
Fax: 859-234-8987
www.bullard.com

Europe:
Bullard GmbH
Lilienthalstrasse 12
53424 Remagen • Germany
Tel: +49-2642 999980
Fax : +49-2642 9999829
www.bullardextrem.com

Asia-Pacific:
Bullard Asia Pacific Pte. Ltd.
LHK Building
701, Sims Drive, #04-03
Singapore 387383
Tel: +65-6745-0556
Fax: +65-6745-5176
www.bullard.com



The Bullard three-rib design is a registered trademark of E.D. Bullard Company.

©2011 Bullard. All rights reserved.

6026131000B (0511)