

CSA Hazardous Locations Approvals

Class I, Division 2, Groups A, B, C, D T6
Class II, Division 2, Groups F, G
Class III
Certificate 2510928

Blower Specifications

- NIOSH-approved
- Single filter design HE and OVAGHE
- “On-board” battery (no external cables)
- Filter locking tab for visual confirmation of correct installation
- 77dBA low battery alarm
- 77dBA low flow alarm
- Active Flow Technology (Mass Flow Sensor Feedback Loop)
- User-selectable two-speed operation:
 - 7.0 CFM/200 LPM
 - 8.5 CFM/240 LPM
- Three lengths available for breathing tubes

**Battery Specifications**

- Lithium Polymer technology
- Fuel gauge to visually indicate remaining capacity
- 4-12 hours of run time on a single battery

Belt Specifications

- Chemically resistant closed cell or vinyl
- Adjustable for waist sizes between 28-inches and 60-inches
- Belt extenders available
- 6.5-inches tall in lumbar region

Charger Specifications

- One-port smart charger with trickle charge mode and optional diagnostics
- Six-port smart gang charger with trickle charge mode

Hood Specifications

- Independent, third party, 1,000 Assigned Protection Factor (APF) available
- Minimum 105 square inches in the viewing lens
- Single- and double-bib hoods available
- Acetate, polyester and PVC lens available
- Loose-fitting facepieces available
- Tychem[®] QC and Tychem[®] SL hoods available
- Pinlock and ratchet suspensions available

Warranty

1 year limited manufacturer warranty for original purchaser from date of purchase

Americas:
Bullard
1898 Safety Way
Cynthiana, KY 41031-9303 • USA
Toll-free within USA: 877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-234-8987

Europe:
Bullard GmbH
Lilienthalstrasse 12
53424 Remagen • Germany
Tel: +49-2642 999980
Fax: +49-2642 9999829

Asia-Pacific:
Bullard Asia Pacific Pte. Ltd.
LHK Building
701, Sims Drive, #04-03
Singapore 387383
Tel: +65-6745-0556
Fax: +65-6745-5176



©2012 Bullard. All rights reserved.
Dupont[™] Tychem[®] is a registered trademark of
DuPont Company